

# Rainbow Fountain Comet Nozzles

## Comet Nozzles



### Comet Nozzles Specifications

- Stainless steel
- Clear stream jet
- Good resistance to wind
- Water level independent
- Adjustable spray angle

Code	BSP. connection	Flow/Head	SPRAY HEIGHT (m)													
			0,5	0,75	1	1.5	2	2,5	3	4	5	6	8	10	12	15
ZF 15-6	1/2"	LPM	7	10	12	15	17									
		Head in mtr	0,5	0,8	1	1,5	2									
ZF 20-8	3/4"	LPM	11	15	19	23	27	31	35	37						
		Head in mtr	0,5	1	1,5	2	2,5	3	4	5						
ZF 25-10	1"	LPM	18	24	27	32	35	40	46	53	60					
		Head in mtr	0,5	0,8	1	1,5	2	2,5	3	4	5					
ZF 25-12	1"	LPM	23	25	27	35	55	58	63	75	87	95				
		Head in mtr	0,6	0,8	1	1,5	2,1	2,5	3,5	5	7	8,5				
ZF 40-13	1 1/2"	LPM			42	46	50	57	63	79	102	120	140	180		
		Head in mtr			1,4	1,8	2	2,5	3	4,8	7	11	19	23		
ZF 40-16	1 1/2"	LPM				80	88	98	118	140	180	200	230			
		Head in mtr				2	2,5	3	4,5	6	8	10	12			
ZF 50-20	2"	LPM						160	200	225	246	270	293			
		Head in mtr							3,5	6	7,5	9,5	11,5	15		
ZF 65-25	2 1/2"	LPM							280	326	369	405	450	490	531	
		Head in mtr								4,6	6	7,5	9	11	16,8	22,5
ZF 80-28	3"	LPM									439	479	552	618	800	880
		Head in mtr										7,1	8,6	12	14	17

## Dimensions

